Certificate of Location of Government Corner

ID#: 712805 **Description:** SEC COR 28 29 32 33 71 **Date Set:** 5/19/1989 **County:** Olmsted

Section: 28 **Township:** 107N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in centerline of E-W twp road and 3' west of centerline of driveway north
County Survey Disk in old CP NW 46.35'
County Survey Disk in PP ENE 83.85'
This corner is located by GPS measurement

Corner History:

9-1853 Gov't Notes William A. Jones, Deputy Surveyor North between sections 32 and 33 75 chs. Enter scattering bur oak timber NW and SE 80 chs. Set section post corner to section 28, 29, 32, and 33 Black Oak 7" N 18° W 110 links Bur Oak 6" S 45° W 39 links Made a trench

6-1881 John Fraser County Surveyor (page 368 No. 359) Found witness tree N 18½° W 110 links. This tree does not agree with stone set by Mr. A. Olds qualified surveyor 18 years ago where Gov't stake stood, and on evidence of Mr. Laird as to fences. Used stone as corner took new witness trees 5" black oak S 51° 45' W 61 links. Set limestone midway and on line as ¼ corner 29, 32, 40.32½ chaines west of stone set by A. Olds.

11-3-1988 County Surveyor dug with backhoe in cut area, found no natural ground left.

5-19-1989 County Surveyor set C.I.M. over ½" re-rod as corner by doubling distance and line from north.

11-15-2005 County Surveyor found CIM in good condition down 0.4'. Red Oak to the SW gone, all other ties ok. Did not check distances.