Certificate of Location of Government Corner

ID#: 713005 **Description:** W SEC COR 30 31 71 **Date Set:** 10/28/92 **County:** Olmsted

Section: 30 **Township:** 107N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The monument is down 0.4'
The corner falls 4 1/2' north of centerline of E-W twp road and 2' west of fence north
Concrete nail in PP #39421 S 36.45'
Traverse point (Mark Shea, 1" square pipe/cap) SE 24.49'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes, John Ball, Deputy Surveyor North between sections 31 and 36. 80.00 chs. Set section corner post. Burr Oak 10 in. N54°W 292 lks Burr Oak 4 in. S60°E 222 lks Burr Oak 14 in. S78°W 385 lks Burr Oak 5 in N2 1/2°E 475 lks

10-1874 Thomas Hunter (P. 262 No. 261), County Surveyor, found stake set by a Mr. Willman from the stumps of 2 bearing trees. Set a stone 5" x 8" x 11" in its place.

5-1887 Thomas Fraser (P. 431 No. 418), County Surveyor, found stone.

6-1893 William Fraser (P. 517 No. 483), County Surveyor, found stone.

5-29-1973 Roger Brand, County Surveyor, found stone and set C.I.M. over it.

9-25-1992 County Surveyor found C.I.M. down 12" leaning north.

10-28-1992 County Surveyor dug out C.I.M., found stone below, reset C.I.M. over stone.

8-20-2010 County survey crew found CIM in good condition