Certificate of Location of Government Corner

ID#: 713006 **Description:** W 1/4 SEC COR 30 71 **Date Set:** 12/17/98 **County:** Olmsted

Section: 30 **Township:** 107N **Range:** 11W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The monument is up 0.2'
The corner falls 1 1/2' west of N-S fence
30d spike in 15" Oak N 13.31'
30d spike in 14" Oak E 11.90'
30d spike in 18" Oak W 24.09'
This corner is located by GPS measurement

Corner History:

9-1853 Gov't Notes: Set post for 1/4 cor. BT: Burr Oak 14" S10°W (or S10°W) 26 links, Burr Oak 14" N60°E 34 links, 18" Burr Oak line tree south 1.40 chains, 10" Burr Oak line tree south 6.70 chains.

5-1887 Thos Fraser (P.431 No.418 S.30) found stone set by Hunter, tested 1 BT just cut correct within link, accepted corner. 1/16 east set stone 8x15x20 at gov't proportions 7 lks short 20.246 then 19.96-3/4 to center.

6-5-1997 Vince Fangman found 4" x 8" x 18" limestone.

12-3-1998 County Surveyor found 3" x 8" x15" limestone found by V. Fangman in 1997 in good condition.

12-17-1998 County Surveyor removed stone and set Cast Iron Cap on telspar pipe at stone location. Set stone on south side of monument. Set post w/sign.

1-5-2011 County survey crew found cast iron cap on telspar pipe in good condition.