Certificate of Location of Government Corner

ID#: 713506 **Description:** 1/4 SEC COR 34 35 71 **Date Set:** 8/23/1977 **County:** Olmsted

Section: 35 **Township:** 107N **Range:** 11W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls on NW side of 20" Black Oak used as CP to fences E-W-S
Post w/sign 2' north
This corner is located by GPS reference stations "Big Bull A & B"

Corner History:

10-1853 Gov't. Notes William A. Jones, Deputy Surveyor North between sections 34 and 35. 40.00 chs. Set a quarter section post from whence a White Oak 10 in. diam. S40ºE 29 lks. White Oak 8 in. diam. S80ºW 16 lks. 44.00 chs. To foot of bluff 100 ft. and enter bottom E&W.

10-1902 William Fraser (P. 26B), County Surveyor, used the corner (no description) to set the Center of Section 35.

8-23-1977 The County Surveyor set a Cast Iron Cap on a square pipe as the corner on the line from the E. 1/4 Cor. Sec. 35 (found) over the Center 35 (found) and in line with the fence south.

11-7-2005 County Surveyor found telspar pipe w/CIC in good condition up 0.3'. All trees with ties are down.

11-15-2005 County Surveyor set post w/sign 2' N.