Certificate of Location of Government Corner

ID#: 713509 **Description:** SEC CEN 35 71 **Date Set:** 8/17/1977 **County:** Olmsted

Section: 35 **Township:** 107N **Range:** 11W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
1/2" iron rod

Reference Ties:

The monument is down 0.2'
The corner falls 22' east of CP to fences N and SE and 17' east of fence north
Spike in W side (up 6') 18" Oak SSW 46.7'
County highway disk in E side 18" Oak SSE 42.58'
Post with sign is north 16'
This corner is located by GPS reference stations

Corner History:

10-1902 W. Fraser (P.26B) set stone and stake at inters 1/4 lines, no mention of W 1/4 cor in survey. 1/16 north, planted stone 19.95 M&L 1316.7. 1/16 east, drove stake 19.93-1/2 M&L 1315.7.

8-17-1977 County Surveyor found small stone over 4"x8"x10" stone 1-1/2' deep 1' N of NW-SE fence. Set 1/2"x2' iron with stone on the S side. Corner 22' E of corner post to fence N and SE and 17' E of line of fence N. RP's: Spike in W side (up 6') of 18" Oak SSW 46.7, Spike and disc in E side 18" Oak SSE 42.58.

8-24-2010 County survey crew found 1/2" iron rod in good condition.