Certificate of Location of Government Corner

ID#: 720106 **Description:** 1/4 SEC COR 1 2 72 **Date Set:** 7/6/1973 **County:** Olmsted

Section: 01 **Township:** 107N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The monument is down 0.5'
The corner falls in line with fence east and 4' west of centerline of N-S road.
Conc. nail in E side PP #33140 NNW 66.0'
20d spike in S side witness tree as taken by T. Fraser E 35.15' (tree is dead)
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes William Jones, Deputy Surveyor South between sections 1 and 2. 40.35 chs. Set quarter section post. Burr Oak 6 in. N20°W 194 lks. Burr Oak 6 in. N50°E 209 lks. 80.35 chs. To section corner.

10-10-1889 Thomas Fraser (p.436 No. 423), County Surveyor, states corner gone in road wash. Ran north-south section line and set a boulder at proportionate gov't measure. Oak 8 in. N89°55'E 52 1/2 lks.

6-1902 Robert Fraser (unrecorded survey in old field book No. 10 P. 42), County Surveyor, could find nothing. Set peculiar limestone as corner from witness tree and testimony of settlers. Remeasured line.

7-6-1973 County Surveyor found limestone and witness tree described in Robert Fraser's fieldbook No.10. Placed stone deep over a drag tooth and set C.I.M. over stone.

7-5-2011 County survey crew found cast iron monument in good condition.