Certificate of Location of Government Corner

ID#: 720406 **Description:** 1/4 SEC COR 4 5 72 **Date Set:** 12/16/2004 **County:** Olmsted

Section: 04 **Township:** 107N **Range:** 12W **Monument Description:** 1" square pipe w/cap RLS #15809

Reference Ties:

The corner falls 3' north of centerline of CSAH 24 and 32' west of centerline of driveway south
County Survey Disk in stub TP #6000-16 SE 76.14'
County Survey Disk in PP #20753 NNE 46.75'
Ref pipe SE 33.14'
This corner is located by GPS measurement

Corner History:

Gov't notes W. A. Jones 1853 North Random 4 & 5 40.00 set a temp. section post south 24; E on true line between Sect. 4 & 5. 40.35 set a section post in mound of earth and sod deposited charcoal made trench and pitts planted osage orange seeds E & W of trench.

11-1891 T. Fraser P 465 No. 447 corner gone in grading road previous year, Mr. Dickerman avers willow row north & fence south equal from orig. corner proved 4 rods set point midway for line W.

10-1894 W. Fraser P 553 No. 510 corner non-existant as before set stone with stake by sub M & L no meas. stone quoted on caption P.465. The caption of P. 465 says 40.11-1/2 West to center sec. 5

11-13-1974 County Surveyor dug with tractor & found nothing, ground was worn out.

8-12-1991 County Surveyor set 1" sq. pipe/cap at Gov't prorated position as also done by W. F. in 1894 when subdividing section 4. This also matches points found and set in the interior of Sec. 4.

5-17-2004 County Surveyor found 1" square pipe w/cap at surface in good condition.

5-24-2004 County Surveyor set reference pipe for 2004 overlay.

12-15-2004 County Surveyor set p.k. nail at surface from 2004 overlay tie-out.

12-16-2004 County Surveyor set 1" square pipe w/cap at surface over pk nail from overlay tie-out. CSD in pp #20753 NE 46.75'. Did not check other tie.

12-4-2006 County Surveyor found 1" square pipe w/cap at surface in good condition.