Certificate of Location of Government Corner

ID#: 720504 **Description:** 1/4 SEC COR 5 8 72 **Date Set:** 6/28/1973 **County:** Olmsted

Section: 05 **Township:** 107N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 3' south of centerline of E-W twp road
16d spike in top center CP N 37.3'
20d spike in NE side root section of large Oak SE 72.0'
1" dia. alum emblem plate in PP #20849 ENE 102.8'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes William Jones, Deputy Surveyor West between sections 5 and 8. 39.92 1/2 chs. Set quarter section post. Burr Oak 6 in. S35°E 162 lks.

1873 Thomas Hunter (P.236 Book A), County Surveyor, found original stake in mound and tested by bearing trees.

11-1891 Thomas Fraser (P.465 No. 447), County Surveyor, located tmeporary corner from SE bearing tree still standing. (Plat shows stone at 1/16 west midway and on line 20.00 chs.)

10-1894 William Fraser found stake and tested with S.E. bearing tree. Set stone and stake as corner.

8-1900 Robert Fraser (P.688 No.611), County Surveyor, found stake and stone.

6-28-1973 County Surveyor dug area of corner but found nothing. Ran line from Sec. Cor. 5-6-7-8 (a stone found) over 1/16 west (a stone found) and doubled measure (1319.62'). Set CIM over reinforcing rod at this location.

12-11-2006 County Surveyor found CIM down 1.0' in good condition.