Certificate of Location of Government Corner

ID#: 720506 **Description:** 1/4 SEC COR 5 6 72 **Date Set:** 7/28/1988 **County:** Olmsted

Section: 05 **Township:** 107N **Range:** 12W **Monument Description:** 1" square pipe w/cap RLS #15809

Reference Ties:

The corner falls 27' WSW of centerline of twp road on curve and 7' south of fence west
County Survey Disk in PP #42099 NW 31.90'
This corner is located by GPS measurement

Corner History:

Gov't Notes W. A. Jones 1853 40.00 set a temp sec. post South 12' East on true line between 5 & 6 40.42 set a sec post Bur Oak 6 in. S 89 E 37 lks. Made trench.

12-1873 T. Hunter P 236 No. 238. Horton found stone in center road. Set as 1/4 corner.

11-17-1891 T. Fraser P 464 No. 446 found stone, limestone found by Hunter P 236.

11-18 & 19 - 1891 T. Fraser P 465 No. 447 found corner P464.

1931 county highway department B 62 P. 8 could not find corner stone assumed corner - Meas. south to section cor. 2649.3 Sp cor P.W. 32.4 - Hub NE 40.1 Meas. east to N-S road at 1/16 cor. 3963.0'

11-1-1974 County Surveyor dug small hole with tractor, found area cut down into almost solid rock, did not find stone.

7-26-1988 County Surveyor dug south of 1974 digging but found bedrock 1/2' deep.

7-28-1988 County Surveyor set 1" square pipe on line from W1/4 6 over the 16th stone found east of the center of Sec. 6 and double the distance from the N-S1/4 line over the 1/16th stone found. RP's centerline of RD north at Rt angles to curve NE 28' corner is 7' south of fenceline west, lines with centerline twp rd north.

12-5-2006 County Surveyor found 1" square pipe w/cap down 1' in good condition.