Certificate of Location of Government Corner

ID#: 720709 **Description:** SEC CEN 7 72 **Date Set:** **County:** Olmsted

Section: 07 **Township:** 107N **Range:** 12W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

Reference Ties:

Corner History:

No Gov't Notes

5-24-1886 T. Hunter P 407 No. 396 set stake at true inters right lines 1/16 west set unmarked stake on line 20.00 then 18.10 (1194.6) to stake on twp line (N89° 50; W) set stakes on line north 1/16 east set stake M & L 19.88 (1312.08) (N89° 50' W) set stakes north.

1931 county highway department B62 P 6 found large boulder in center road on E-W fence line set iron pipes east and west 33' Sta. 80 + 12.3 . Meas. North 2633.0 Sta. 106 + 45.3 PI alfa 0° 4' Lt. Corner could be 2' North of line E-W fences.

1951 county highway department found boulder placed 1" steel riser. Disc top fence post E50.04 Disc top fence post SW 67.92 Hub in fence line W 84.95

10-28-1977 Ron Olson used computed center location.

7-30-1996 County Surveyor dug at dip in line of fence west and east Fd only string line nails Fd nothing further.