Certificate of Location of Government Corner

ID#: 721004 **Description:** 1/4 SEC COR 10 15 72 **Date Set:** 5/9/97 **County:** Olmsted

Section: 10 **Township:** 107N **Range:** 12W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls in line with fence north and 2' south of main line of fence east
County Survey Disk in CP N 3.38'
Post w/sign 2' north
This corner is located by GPS reference stations "Axley I & II"

Corner History:

1853 Gov't Notes W. A. Jones East random 10 & 15 bar 8 ° 48' E 40.01-1/2 Set a sect. post Bur Oak 7 in. N 25 W 31 lks. Bur Oak 8 in. S 76 W 47 lks. 58.00 Enter thicket N & S.

5-1902 Armstrong P52B S 16 A Mullholland, J. Patchen In placing NE cor 16 meas. to above corner 39.60 found stone west side road. 3"x12" setting in E-W direction. 30' east of cor. post of fence on west side of road. -Meas. south to stone S1/4 15 80.05.

12-2-1996 County Surveyor set out M & L between sec. corners. This came on east side of old road +-3' south of line of fence E. We also set up prorated C.A. distance from west which came on west edge of old road 19.54' west of M & L point nearly in line of fence running north.

5-9-1997 County Surveyor dug at C. Armstrong stone found position from (1902). Doug from 2' north to 3' south + 2' E & W of comp. location. 1-1/2' deep to clean clay. Found nothing. We probed area but unlikely the stone could still be here. The remains of old N-S road is 2'-3' lower than the natural ground level east & West. Set cast iron cap on telspar pipe as corner on E-W sec. line & C.A. Prorated dist. from West at Called location at west side old road. This falls in line of fence north and 2' south of mainline of fence east. Set sign & post 2' north of Mon.