Certificate of Location of Government Corner

ID#: 721109 **Description:** SEC CEN 11 72 **Date Set:** 6/26/1893 **County:** Olmsted

Section: 11 **Township:** 107N **Range:** 12W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
2 1/2"x5" stone with 3/4" square iron on south side and 5/8" rerod on north side

Reference Ties:

The corner falls 20' E of N-S fence.
This corner is located by GPS measurement

Corner History:

No Gov't Notes

6-16-1893 W. Fraser P 518 No. 484 set stone 1-1/2 x 5 x 24 at inters lines.
-1/16 north set stsone 2 x 6 x 20 M & L 19.88-1/2 (1312.41)
-1/16 south set stone 2 x 6 x 20 M & L 19.89 (1312.74)
-Set 1/64 stake south above 1/16 cor. M & L 9.94-1/2 (656.37)
-1/16 east set stone 4 x 8 x 16 M & L 19.97-1/2 (1318.35)
-1/16 center SE1/4 Sec. 11 set boulder 8 x 18 x 18 inters lines bearing N & S N22' E at center (S89° 40' E) at S line.
-Set 1/64 south above 1/16 cor. stone 2 x 8 x 22 M & L N-S 1/16 line 9.94 (656.04')

11-2-1981 County Surveyor found recorded 2-1/2" x 5" stone. Drove 3/4" square iron on the south side of stone and set a 5/8" rod on the N. side . Corner falls under the N-S fence and 20' south of a large old corner post in the N-S fence line.

3-17-2010 County survey crew found 2-1/2" x 5" stone down 0.1' in good condition.