Certificate of Location of Government Corner

ID#: 721304 **Description:** 1/4 SEC COR 13 24 72 **Date Set:** 6/2/88 **County:** Olmsted

Section: 13 **Township:** 107N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 6' west of centerline of CR 107 and 1' north of fence west
Punch hole in top center 15" CMP E 18.74'
Punch hole in top center 15" CMP W 11.65'
5/8" pipe under fence W 60.0'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes: 39.98-1/2 set a 1/4 sect post at average distance in mound of earth and sod. Deposited charcoal, made trench and pits, planted Osage Orange seeds N and S of trench.

6-1893 W. Fraser P.514 No.481 corner gone. Set stone 2-1/2x12x12 M&L 39.91-1/2 . 1/16 west drove unmarked stake M&L 19.95-3/4 . 1/16 south drove unmarked stake M&L no meas line W . 1/16 center NW 1/4 24 set boulder stone inters lines.

6-1893 W. Fraser P.516 No.482 used corner, no particular mention of corner. Meas east and west 39.91-1/2

7-23&24-1973 County Surveyor ran traverse from south to nail set in line fence west near west side of road 18" culvert near. Dug massive hole up to 7' deep on N and S sides of culvert, found recorded stone nail. Corner in fair line fence west and 3' west of center road. Broke glass on stone.

9-1978 county highway department found 5/8 re-bar, took add'n ties. Punch mark on top culv west 11.62', punch mark on top culv east 18.69'.

6-2-1988 County Surveyor reset small rod found. Set CIM over rod found.

8-9-2007 County Surveyor found CIM down 0.7' in good condition.