Certificate of Location of Government Corner

ID#: 721306 **Description:** 1/4 SEC COR 13 14 72 **Date Set:** 8/10/2007 **County:** Olmsted

Section: 13 **Township:** 107N **Range:** 12W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

County Survey Disk in SE side 30" Oak SW 21.57'
County Survey Disk in N side 20" Oak W 9.34'
County Survey Disk in SE side 26" Oak NE 23.92'
This corner is located by GPS reference stations "Bow D & E"

Corner History:

1853 Gov't Notes: Jones, set 1/4 sect post M&L 40 chains 2640' from south. 9" Bur Oak S60E 115 lks. 14" Bur Oak S30W 105 lks.

6-1893 W. Fraser P.516 No.482 found stake but it had been moved by rubble from stone quarry. Set stone 3x12x30 from NW BT and stump of SE BT. New BT 6" Burr Oak S72°W 14 links 9.24'. 1/16 south set stake M&L 19.95 1/16 north found stone set by Hillman in early day, accepted by all, no N-S meas. 1/16 center NW 1/4 13 found stone set drove stakes east of above 1/16 cor 9.97 then 498-1/2 then 4.98-1/2 to 1/16 corner on sec line, a stone found. 1/16 west set stone M&L 20.00. 1/16 south found stake M&L 19.95 P.516. 1/16 center SE 1/4 14 set boulder 2x12x16.

7-17-1973 County Surveyor meas S from centerline E-W road (no meas ever given) found 4 way fence anchored to 20" ± burr oak at about 1318± which proved to be witness tree mentioned by W. Fraser then 6" oak. Found good part of recorded 3x12x30 stone at edge of low level area believed to be old farm quarry. Almost exact bearing and meas to tree. Fence anchored to tree a conveince as fence straight and true until it hits woods and sloping area at 1200' ± then cuts over. No RP's, left stone open or iron on corner.

8-10-2007 County Surveyor found 3"x12"x30" stone down 0.5' in good condition. Set a 3' telspar with CIC up 0.3' at stone location.