Certificate of Location of Government Corner

ID#: 721506 **Description:** 1/4 SEC COR 15 16 72 **Date Set:** 11/3/1976 **County:** Olmsted

Section: 15 **Township:** 107N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 10' north of fence west and 3' east of N-S fence
County Survey Disk in N side blazed 30" Burr Oak ESE 142.5' (Slope)
County Survey Disk in SW side blazed 23" Burr Oak SE 133.45' (Slope)
Iron CP SSW 10.1'
Post w/sign 1 1/2' east
This corner is located by GPS measurement

Corner History:

10-1853 Gov't Notes William A. Jones, Deputy Surveyor North between sections 15 and 16. 40.00 chs. Set a quarter section post. Burr Oak 12 in. S40° E 228 lks. Made a trench.

7-1870 Robert Perry (P.130 No. 162), County Surveyor, found the original stake standing. Set a new stake and set the original stake beside it.

5-1902 Charles Armstrong, (P.52B), County Surveyor, found the remains of the stake P. 130 between two corner posts. Set a stone in its place.

5-1965 John Kerr, County Surveyor, looked for the corner but did not find it.

11-3-1976 County Surveyor found a 5"x9"x12" limestone over 3" of old stake. Also found the remains of the old posts on the North and South sides as recorded by Armstrong. Set a C.I.M. over a 1/2"x2' rod driven in the stake hole. Set the stone on the South side of the C.I.M.

11-7-1996 County Surveyor found CIM set in 1976 at stone location. Set post and sign 1-1/2' east of monument. The corner falls 10' north of fence line west and 3' east of N-S fence line.

7-12-2011 County survey crew found cast iron monument at the surface in good condition.