Certificate of Location of Government Corner

ID#: 721604 **Description:** 1/4 SEC COR 16 21 72 **Date Set:** 12/7/89 **County:** Olmsted

Section: 16 **Township:** 107N **Range:** 12W **Monument Description:** 5/8" brass plug

Reference Ties:

The corner falls in centerline of CSAH 2 and 3' east of centerline of twp road north
NE cor. old creamery bldg (up 4') NW 111.85'
SW Cor of front jog old creamery bldg WNW 105.99'
County highway disk in PP SW 111.65'
NW corner of house NE 138.13'
This corner is located by GPS measurement

Corner History:

10-1853 Gov't Notes William A. Jones, Deputy Surveyor West on true line between sections 16 and 21. 39.985 chs. Set a quarter section post. Enter prairie bottom North and South. Burr Oak 8 in. N17°W 296 lks. Burr Oak 7 in. S50°W 180 lks.

7-1870 Robert Perry (P. 130 No. 162), County Surveyor, states corner gone. Set a 3"x6"x23" stone midway and on line.

5-1902 Charles Armstrong (P. 52B), County Surveyor, found a stone as recorded P. 130.

5-1964 John Kerr, County Surveyor, found a pipe said used by the Co. Hwy. Dept. and others as the corner. Set a C.I.M. over a steel rod as the corner.

11-9-1976 County Surveyor dug along the South side of a pipe found in the centerline of Co. Rd. #2. Found Perry's recorded stone 4' deep with a stake on the South side. Removed the pipe and a rod found beneath it which were 1.05' North and .7' West of the stone. Put scrap iron around the stone and set a C.I.M. over all.

CORRECTION OF CORNER: Correct corner is 1.05' south and .7' East of the Co. Hwy. Dept's and John Kerr's location

12-7-1989 county highway department set 5/8" brass plug, RP's: SW cor of front jog old creamery bld WNW 105.99'. NE cor creamery bld (up 4') NW 111.85'. county highway department disc in PP SW 111.65'.

12-12-2006 County Surveyor found 5/8" brass plug at surface in good condition.