Certificate of Location of Government Corner

ID#: 721609 **Description:** SEC CEN 16 72 **Date Set:** 6/27/73 **County:** Olmsted

Section: 16 **Township:** 107N **Range:** 12W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
5/8" square head lag bolt

Reference Ties:

The monument is down 1.0'
Disc in TP NNE 33.8'
Disc in TP NE 135.4'
Disc in TP SE 158.9'
The monument is 2.5' west of centerline n-s road and 15.5 north of field drive east.
This corner is located by GPS measurement

Corner History:

7-7-1870 R. Perry P.130 No.162 set post marked 14" B Oak N89-1/4E 2.33 chs. 1/16 east set post 19.86 (1310.8) M&L to original corner found.

5-1902 Armstrong P.52B found corner P.130 used to set 1/4 north by projecting from S 1/4 16 over center 16 (this corner). Found stone at center 16. 1/16 north set boulder 6x10x30 M&L 19.77-1/2 (1305.15). 1/16 south found stone M&L no measure. 1/14 corner east found stake set stones no meas no E-W run line.

5-21-1964 J. Kerr found stone and stake 2' deep next to rock subsoil set CIM over same.

6-27-1973 County Surveyor found CIM 10" deep. Set 5/8" square head lag bolt 8" long riser. All RP's still in tree now stump with drag tooth gone.

8-18-2010 County survey crew found 5/8" sq. lag bolt in good condition.