Certificate of Location of Government Corner

ID#: 721804 **Description:** 1/4 SEC COR 18 19 72 **Date Set:** 12/7/89 **County:** Olmsted

Section: 18 **Township:** 107N **Range:** 12W **Monument Description:** 5/8" brass plug

Reference Ties:

The corner falls in centerline of CSAH 2
Top center tel. riser S 58.64'
County highway disk in PP SE 71.97'
Ref pipe NE 161.38'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes William Jones, Deputy Surveyor East on true line between 18 and 19. 38.38 chs. Set a quarter section post in mound of earth and sod. Deposited charcoal. Made trench and pits. Planted osage orange seeds north and south of trench. 78.38 chs. To section corner.

7-1874 Thomas Hunter (P. 258 No. 258), County Surveyor, found mound with pole in center claimed by a Mr. Howard to be where stake stood.

6-1876 Thomas Hunter (P. 298 No. 293), found stake driven by Mr. Howard. Set stone 3"x10"x20" with broken brick around and below stone.

5-1886 T. Hunter (P. 408 No. 396) found stone set P. 298.

6-1924 county highway department (Book 42 P.10) found stone. Took witness trees: Willow 10 in. S 64.9' White Pine 12 in. N.E. 62.2'

1930 county highway department (Book 62 P.3) could not find stone but found old P.I. and a few pieces of brick.

11-16-1973 County Surveyor found iron set by Co.H.D. and stump of willow tree used as witness tree by county when stone was in place. Corner stone gone. Accepted Co. H.D. location and reset corner with C.I.M. over iron.

8-8-1986 County Surveyor set transit tie 3/4" pipe w/cap. Pipe to 1/4 cor 161.38'

12-7-1989 county highway department set 5/8" brass plug in centerline CR #2. RP's: county highway department disk in PP SE 71.97', top center tel riser S 58.64'.

7-11-2002 County Surveyor found brass plug in good condition.

5-17-2004 County Surveyor found 5/8" brass plug at surface in good condition.