Certificate of Location of Government Corner

ID#: 721805 **Description:** W SEC COR 18 19 72 **Date Set:** 12/7/89 **County:** Olmsted

Section: 18 **Township:** 107N **Range:** 13W **Monument Description:** 5/8" brass plug

Reference Ties:

The corner falls in centerline of CSAH 2
County highway disk in CP SW 69.59'
County highway disk in PP NE 76.86'
County highway disk in Apple tree NW 64.46'
Ref. pipe S 282.26'
This corner is located by GPS measurement

Corner History:

Gov't Notes: 80.00 sec post for quarter section corner 13-18-19-24. Bur Oak 10 N 65 W 155. Bur Oak 12 S 88 W 185. Burr Oak 10 S 8-1/2 E 213. Bur Oak 8 N 25 E 381.

7-1874 T. Hunter P.258 No.258, corner gone, found stump SW BT also NE BT hole where stump grubbed out. SE and NW B trees gone. Set stone 4x5x14 at location gov't notes. Meas west 39.82 (2628.12) to point set from B T stump. Meas south 39.96-1/2 (2637.69) to stone 4x8x26 set M&L.

6-1876 T. Hunter P.298 No.283 found stone P.258, broken and partly washed away, set new stone 4x5x27 in its place. 1/16 east set stone 4x7x16 M&L 19.06-3/4 N89° 45 W. This stone placed midway by instructions of owners SW 1/4 18. Meas north 39.94 to stone set replacing stake.

1937 county highway department B.92 P.78 found nothing set limestone 4x10x15 with cross. Sp cor post N 28.2 + headwall culv SW 52.6. Sp cor post SE 58.2, hub north N 63.9 ?P.I.?. Later ties, nail in tele pole SE 41.1, Sp top cor fence post SW 45.9. Set 1/3 meas W 1/4 18 to W 19-30 2636.93 and on direct twsp line.

4-21-1958 Found 5/8" rod.

9-1968 J. Kerr found stone at W 1/4 19 2.4 N and 2.2 W of Co corner. Stone to SW 19 1638.7 if double meas would come 4' N and 4.4' W of where county set corner. Either big kink in twsp line at W 18-19 or SW cor 19 boulder not true corner. Corner if ther very deep. McGhie set rod (see survey sheet) 1958 April 1st.

8-25-1976 County Surveyor dug 4' to 12' from 5' E of McGhie rod W and from McGhie rod N. Found county highway department stone .21' N of rod and 6' deep. Found remaining 24" of Hunter's 4"x5"x27" stone (broken) 5.7' W and 3.5' N of rod and 7' deep. Set county highway department stone (4"x10"x15" with cross) on S side of Hunter's stone and reinforcing rod on E side.

9-1-1976 County Surveyor set 1/2"x24" rod. Corner 1' W centerline road S and 1' N centerline E-W road. RP's: Punch hole top W end of 24" CMP to road S SW 35.91. Punch hole top S end of 36" CMP to road E SE 48.10. CSD SE side of PP #19409 NE 44.50. 1/16 E (8-31-76) Dug with backhoe from a pt 2' W of traverse nail W for 8' and N for 4' by 4-1/2' deep to clay. Found old road on clay. Scrapped and found mark in clay approx 4"x7" as described by Hunter 1.1' N and 7.35' W of T.N. Dug to cover M&L .

8-7-1986 County Surveyor set transit ties 3/4" pipe w/cap west of PP SE property corner to Robert P. Schmidt property. RP to 3/4" pipe CSD in PP #19431 east 28.47'. Angle at 3/4" pipe, angle RT 143° 07' 14" most northerly and shortest radio tower in sec 26 107-13 to W sec cor 18-19. Viola 282.26'

12-7-1989 county highway department set 5/8" brass plug in centerline CR #2. county highway department disc in c.p. SW 69.59'. county highway department disc in PP NE 76.86'. Spike and county highway department disc in Apple tree NW 64.46'.

7-10-2002 County Surveyor found brass plug in good condition.