Certificate of Location of Government Corner

ID#: 721905 **Description:** W SEC COR 19 30 72 **Date Set:** 6/3/75 **County:** Olmsted

Section: 19 **Township:** 107N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in centerline of N-S twp road
County Survey Disk in PP #19447 SSW 77.76'
NE Corner of metal shed SE 103.2'
Center 10" Pine N side of fence E 65.5'
This corner is located by GPS measurement

Corner History:

10-1853 Gov't Notes Ball, Deputy Surveyor North between 25 and 30. 80.00 chs. Set Corner post. Bur Oak 14 in. N3&3/4°W 716 lks. Bur Oak 10 in. S1&1/2°W 130 lks. Bur Oak 14 in. S4°E 120 lks. Bur Oak 12 in. N3&1/2°E 710 lks.

6-1873 Thomas Hunter (P.227 No.230), County Surveyor, found short stake in ground with stones sunk around it. Tested stumps of bearing trees still in place and found corner correct.

5-1874 T. Hunter (P.242 No. 243) found stake and stones P.227.

7- 1874 T. Hunter (P. 258 No. 259) found stone set and described P. 227.

1937 county highway department (B.92 P.78) found 6"x6"x14" pointed boulder avered by Mr. Wiese as corner.

9-10-1968 John Kerr, County Surveyor, found Co. Hwy. Dept. boulder and stake. Set 1/2" rod where corner was found.

6-3-1975 County Surveyor found Kerr's 1/2" rod and checked references. Removed rod and set C.I.M.

7-10-2002 County Surveyor found CIM in good condition.