Certificate of Location of Government Corner

ID#: 722004 **Description:** 1/4 SEC COR 20 29 72 **Date Set:** 5/29/74 **County:** Olmsted

Section: 20 **Township:** 107N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls under N-S fence
County Survey Disk in W side 5" cedar post S 2.5'

Corner History:

1853 Gov't Notes William Jones, Deputy Surveyor
West on true line between 20 and 29. 40.05 chs. Set a quarter section post. Burr Oak 9 in. S75°E 280 lks. Burr Oak 10 in. S36°W 152 lks. 80.10 chs. Section corner.

5-1886 Thomas Hunter (P.409 No. 398), County Surveyor, states corner plowed out, land cultivated, bearing trees gone. Set a temporary corner midway and on line.

6-1902 Charles Armstrong (Book B P. 58), County Surveyor, found stake and stone avered by a Mr. Newman as 2' too far west.

6-1902 Armstrong (P. 60 Book B), County Surveyor, found stone and stake.

5-22-1974 County Surveyor dug and found an old post stub but did not use as corner.

5-29-1974 County Surveyor reset the corner by intersecting the north-south 1/4 line of Section 20 with the section line between sections 20 and 29. Set a C.I.M. over a 1/2"x15" iron rod. Corner location very near old post stub.

6-30-2011 County survey crew found cast iron monument down 0.7' in good condition.