Certificate of Location of Government Corner

ID#: 722006 **Description:** 1/4 SEC COR 19 20 72 **Date Set:** 5/22/74 **County:** Olmsted

Section: 20 **Township:** 107N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 4' east of centerline of CR 102 and in line with fences east and west
County Survey Disk in S side PP W 30.93'
County Survey Disk in W side PP SSE 179.1'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes William A. Jones, Deputy Surveyor North between sections 19 and 20.
40.00 chs. Set a quarter section post in mound of earth and sod. Deposited charcoal. Made trench and pits and planted orange seeds east and west of trench.

7-1874 Thomas Hunter (P. 285 No. 258), County Surveyor, found original stake in mound with pits plain.

5-1886 Thomas Hunter (P.409 No. 398) found stone set in center of road in line with the fence running west.

6-1903 Charles Armstrong (P. 60 Book B), County Surveyor, found stone in the center of the north-south road and set a new stone 5"x12"x14" which lay 49 lks. from the west fence of the road.

5-22-1974 County Surveyor found limestone 1' deep. Set 1/2"x2' rods on the east and west sides of the stone and set a 10" C.I.M. Corner falls in the east wheel track and in line with the east-west fence.

7-20-2002 County Surveyor found CIM in good condition.