Certificate of Location of Government Corner

ID#: 722009 **Description:** SEC CEN 20 72 **Date Set:** 5/18/64 **County:** Olmsted

Section: 20 **Township:** 107N **Range:** 12W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
Cast Iron Monument

Reference Ties:

The corner falls 6' east of fence north and 6' east of CP

Corner History:

5-28-1886 T. Hunter P.409 No.398 set temp stake at inters lines, did not set perm corner to spite those who it would benefit as they wouldn't pay. 1/16 west set temp stake 20.04-1/4 M&L for line S S89° 35' E. 1/16 east set temp stake 19.97-1/2 M&L for line W due north.

6-1903 C. Armstrong P.60B set 3x12x14 limestone inters lines, this comes in line fences E-W but 8-1/2' east of fence running north. 1/16 south set stone 3x12x14 M&L 19.88 then set stone 3x4x10 as 1/64 cor on line 9.94 south above 1/16 cor.

5-18-1964 J. Kerr B.88 P.19 used corner in survey found after meas from east and noting distance recorded east of north fence. Set CIM over rod below surface. Corner lines good fence running west. Corner lies 6.0' east of fence running north. No fence south, very poor fence east. Kerr book 88 p.19 says found limestone at cen 20 6' E of steel cor fe post.

9-27-1978 McGhie & Betts found and used monument at center of section 20.

6-30-2011 County survey crew found cast iron monument down 1.4' in good condition.