Certificate of Location of Government Corner

ID#: 722109 **Description:** SEC CEN 21 72 **Date Set:** 1/16/2002 **County:** Olmsted

Section: 21 **Township:** 107N **Range:** 12W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
5/8" pipe w/cap RLS #26371

Reference Ties:

The monument is down 0.1'
The corner falls 13' east of centerline of N-S twp road and 6' north of fence west.
This corner is located by GPS measurement

Corner History:

7-7-1870 Perry P.130 No.162 set stone 5x5x28 at true inters lines made pits also set stake marked no meas.

3-18-1896 W. Fraser P.593 No.589 found stone P.130 found stone to be 12 links too far west to be on direct line 1/4 corners, left as found. This could be as S 1/4 21 set this survey set M&L on south line 21 while Perry found original stake there.

5-28-1974 County Surveyor dug for Perry's stone, did not find. Ran N-S 1/4 line after finding W. Fraser's iron stake at S 1/4 cor 21. Line between 1/4 corners falls on E shoulder of N-S road and W. Fraser's msmt (prorated) would fall about 3' N of fences E & W. Did not set corner E 1/4 cor not found at this time.

1-16-2002 Brand & Massey Surveying Inc. set 5/8" pipe w/cap #26371 at intersecting quarter lines at center of section 21.

8-18-10 County survey crew found 5/8" pipe with cap RLS 26371 in good condition