Certificate of Location of Government Corner

ID#: 722204 **Description:** 1/4 SEC COR 22 27 72 **Date Set:** 11/18/1976 **County:** Olmsted

Section: 22 **Township:** 107N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 40' east of centerline of TH 42
PI rod in SBL of TH 42 WSW 44.77'
County Survey Disk in S side 18" Pine up 0.6' E 45.45' (grown over, bent)
This corner is located by GPS measurement

Corner History:

10-1853 Gov't Notes William A. Jones, Deputy Surveyor West on true line between sections 22 and 27. 40.015 chs. Set a quarter section post. Burr Oak 9 in. N26°W 16 lks. Burr Oak 6 in. S7 1/2°E 111 lks. 80.03 chs. To section corner.

5-1872 S. Hillman (in 1890 letter on record), a surveyor, found the Gov't stake. Set a large stone at the quarter stake. Set a stone 1 1/2 lks. broad and 5 1/2 lks. long at the Center of Section 22.

6-1885 Thomas Hunter (unrecorded survey in Old Field Bk. #14 P. 39), County Surveyor, found stone set by Hillman. State Hwy. 42 R/W map shows corner 48' East of the centerline P.I. and in the center of the old road which was assumed to be on the N-S 1/4 line.

11-17-1976 County Surveyor dug with the backhoe but could find no evidence of the corner.

11-18-1976 County Surveyor set a CIM over a 1/2"x2' rod as the corner on line from the 1/16th North (found) of the Center of Section 22 over the Center of Section 22 (found) and in line with the fence East.

1-9-2007 County survey crew found CIM down 0.4' in good condition.

5-9-2008 County survey crew found cast iron monument down 0.5' underwater in bottom of ditch.

6-22-2011 County survey crew found cast iron monument in good condition

7-7-2016 County survey crew found cast iron monument in good condition