Certificate of Location of Government Corner

ID#: 722206 **Description:** 1/4 SEC COR 21 22 72 **Date Set:** 11/1/1976 **County:** Olmsted

Section: 22 **Township:** 107N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The monument is down 0.1'
The corner falls 2' west of N-S fence, in line with fences far west and east and 2 1/2' WSW of 7" sq. Brace post in N-S fence
Blazed 23" Burr Oak N30°W 93.55'
County Survey Disk in E side blazed 10" Burr Oak N 29°W (Mag.) 13.85'
County Survey Disk in W side blazed 10" Burr Oak S 13 1/2°W (mag.) 95.07'
County Survey Disk in SW side blazed 17" Burr Oak S 29° E (mag.) 64.35'
This corner is located by GPS reference stations.

Corner History:

10-1853 Gov't Notes William A. Jones, Deputy Surveyor North between sections 21 and 22. 40.00 chs. Set a quarter section post. Burr Oak 10 in. N40°W 100 lks. Burr Oak 11 in. N10°E 156 lks.

7-1870 Robert Perry (P.130 No. 162), County Surveyor, found a stone beside the original stake. Tested correct by the stumps of two bearing trees.

11-1-1976 County Surveyor found a 2 1/2"x7"x30" stone. Set a C.I.M. over a 1/2"x2' rod as the corner with the stone (broken in two pieces) on the south side of the C.I.M.

6-30-2011 County survey crew found CIM in good condition.