Certificate of Location of Government Corner

ID#: 722504 **Description:** 1/4 SEC COR 25 36 72 **Date Set:** 7/31/73 **County:** Olmsted

Section: 25 **Township:** 107N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The monument is down 0.4'
The corner falls 1 1/2' south of centerline of E-W twp road and in line with fence north
Concrete nail in PP #513 WSW 31.20'
20d spike in 36" Oak N 44.49'
Concrete nail in SE side TP NE 62.2'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes West between sections 25 and 36. 40.00 chs. Set a quarter section post in mound of earth and sod. Deposited charcoal, made trench and pits, and planted osage orange seeds north and south of trench. 80.00 chs. to section corner.

6-1893 William Fraser (P. 517 No. 483), County Surveyor, found stone as corner claimed by settlers as true corner.

7-31-1973 County Surveyor dug in center of road and found 4"x6" topped limestone. Drove 1/2"x12" pipe on east side of stone with C.I.M. above.

9-25-1992 County Surveyor found CIM in good condition. New RP's: monument 1-1/2' south of centerline E-W road conc nail in PP #513 WSW 31.20', 20d in 36" oak north 44.49'.

8-20-2010 County survey crew found CIM in good condition