Certificate of Location of Government Corner

ID#: 722705 **Description:** SEC COR 27 28 33 34 72 **Date Set:** 5/28/1974 **County:** Olmsted

Section: 27 **Township:** 107N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 8' north of centerline of E-W twp road and in line with fence north
County Survey Disk in 6" Oak NE 35.62'
20d spike in 15" Oak ENE 87.4'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes William Jones Deputy Surveyor North between sections 33 and 34. 80.00 chs. Set a section corner post. Burr Oak 9 in. N52°W 207 lks. Burr Oak 10 in. N46°E 170 lks. Burr Oak 9 in. S20°E 123 lks. Burr Oak 8 in. S55°W 99 lks.

3-1879 Thomas Hunter (P. 354 No. 346), County Surveyor, found stone in center of road. Tested stump of NE bearing tree and the places where the SE and SW bearing trees had been grubbed out. These proved stone to be correct.

5-1880 John Fraser (p. 364 No. 355), County Surveyor, found stone avered by E.A. Doty as set by a Mr. Hillman at the site of the gov't stake.

5-27-1971 County Surveyor dug with Forest Wharton cat prior to road grading and found a 2"x10"x10" vertical limestone. Removed the stone and set a 2"x2"x16" hub with a wine bottle on top.

5-28-1974 County Surveyor dug hole with backhoe to locate wine bottle over hub. Reset the wine bottle over a 3/4" rod with a CIM over all.

6-17-2008 County Surveyor found CIM down 0.5' in good condition.