Certificate of Location of Government Corner

ID#: 722804 **Description:** 1/4 SEC COR 28 33 72 **Date Set:** 5/28/74 **County:** Olmsted

Section: 28 **Township:** 107N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The monument is down 0.5'
The corner falls 1' south of centerline of E-W twp road
Punch hole in W end 15" CMP SW 25.06'
Punch hole in E end 15" CMP SE 31.86'
3/4" pipe under fence N 50.0'
5/8" ref. iron S 90.0'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes William A. Jones, Deputy Surveyor West on true line between sections 28 and 33. 39.985 chs. Set a quarter section post in mound of earth and sod. Deposited charcoal. Made a trench and pits. Planted osage orange seeds north and south of the trench. 79.97 chs. to section corner.

5-1880 John Fraser (P. 364 No. 355), County Surveyor, found old stake. Set a 2"x8"x30" stone by old stake.

8-26-1968 John Kerr, County Surveyor, dug with tractor and found stone of recorded size broken up by post. Put pieces of stone and glass by C.I.M. with sash weight under C.I.M.

5-27-1971 County Surveyor removed C.I.M. for grading road.

5-28-1974 County Surveyor dug down and found sash weight and stone pieces. Reset a C.I.M. over a 1/2" rod.

8-18-2010 County survey crew found CIM in good condition