Certificate of Location of Government Corner

ID#: 722805 **Description:** SEC COR 28 29 32 33 72 **Date Set:** 8/16/68 **County:** Olmsted

Section: 28 **Township:** 107N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The monument is down 1.0'
SE corner 10" square conc post NW 46.9'
Bottle cap in PP #20541 NE 45.6'
Center S end 18" culvert SE 24.2'
Cap in brace PP #20542 SE 45.85'
Corner falls in center of intersection of roads N-S-E-W township roads

Corner History:

1853 Gov't Notes: W.A. Jones. North sect 32 and 33. 80.00 set a section corner post to 28-29-32- & 33. Bur Oak 8 in. W4W 83 lks. Bur Oak 10 in. N50E 206 lks. Bur Oak 6 in. S112E 98 lks. Bur Oak 24 in S65W 277 lks.

6-1873 T. Hunter P.226 No.229 found short stake in center road avered by R. Calvert to be where original corner stood (stone marked on plat). Meas south 39.84 to 1/4 cor set midway (not line). Meas west 40.13 to original stake in mound.

5-1880 John Fraser P.364 No.355 found stake set by Hunter p.226. 1/16 south set stone M&L 19.81-1/2.

6-1902 C. Armstrong P.58B found stone in center road. Meas west 40.13 to 1/4 stone set. Meas north 39.89 to temp point set midway only.

1930 county highway department found limestone

8-16-1968 J. Kerr dug extensively with tractor found stone and 1x2 hub by side all references gone. SE corner 10" square conc post NW 46.9'. Teem cap in power pole 20541 NE 45.6. center south end 18" culv SE 24.2'. Cap on brace pole power pole 20542 SE 45.85'.

7-3-1989 T. Ferguson used monument for survey in NW 1/4 Sec. 33.

8-17-2010 County survey crew found CIM in good condition.