Certificate of Location of Government Corner

ID#: 722904 **Description:** 1/4 SEC COR 29 32 72 **Date Set:** 8/16/68 **County:** Olmsted

Section: 29 **Township:** 107N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The monument is down 1.2'
The corner falls 1' north of centerline of E-W twp road and 5' east of field division north
SW corner 10" concrete CP NE 38.5'
Bottle cap in center 8" cedar post NNW 32.8'
Bottle cap in W side PP #20532 NW 44.3'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes: W.A. Jones. 40.02-1/2 set a 1/4 section post in mound of earth and sod. Deposited charcoal, made trench and pitts, planted Osage Orange seeds N and S of trench.

6-1873 T. Hunter P.226 No.229 found original stake in mound at fence corner. 1/16 south set stake M&L 19.92-1/2 N10'W.

6-1902 Armstrong P.58B examined area carefully by digging in area of line of fence running north. Found nothing. Meas south sec line 29 80.26 (2648.58) set limestone 4x14x28 M&L corner came 10" east and 51 lks south fence corner of fence running north. 1/16 north set limestone 2x10x20 pointed at upper and lower ends M&L 19.90. Corner came 4" east of fence row running north. Meas east and west M&L 40.13 2648.6.

8-16-1968 J. Kerr dug with tractor found stone easily, set CIM over stone and glass. SW corner 10" conc cor post NE 38.5. Bottle cap center 8" cedar post 5" west of N 32.8'. Bottle cap west side power pole No. 20532 NW 44.3'. Corner lies 1' north center road 5' east of fence north.

8-18-2010 County survey crew found CIM down 1.2' in good condition.