Certificate of Location of Government Corner

ID#: 722905 **Description:** SEC COR 29 30 31 32 72 **Date Set:** 8/16/1968 **County:** Olmsted

Section: 29 **Township:** 107N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in centerline of CR 102 and 2' south of centerline of E-W twp road
NW corner 10" concrete CP SE 50.45'
County highway disk in S side PP #20482 SW 41.9'
County highway disk in SW side PP #20492 NW 39.0'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes: W.A. Jones, 80.00 set a corner section post to section 29-30-31-and 32 and deposited charcoal, made trench and pitts, planted Osage Orange seeds NW and SE of trench.

9-1863 P.C. Compton P.77 No.114 shows sec corner (see survey for breakdown of sec 31)

5-1872 T. Hunter P.206 No.214 found remains of old stake in center mound and pitts, set stone 3x6x26. Meas west 39.57 to N 1/4 31 stone 2-1/2x7x20 set. Meas south 39.84-1/2 to temp stake set M&L.

6-1873 T. Hunter P.227 No.230 found stone set P.206 Measured already fenced school lands. 6.82 450.12' north 10.85 716.1' west of sec corner. Meas north 40.00 to E 1/4 30 assumed stake.

6-1873 T. Hunter P.226 No.229 found stone set P.206. 1/16 south set stake M&L 19.92-1/4.

6-1902 C. Armstrong P.58B found stone in center road. Meas east 40.13 M&L 2648.6 1968 2653.0. 1/16 north set limestone 4x8x16 M&L 19.97 for line east.

6-18-1968 J. Kerr found stone easily with tractor digger. Corner lies in centerline N-S road about 2' south centerline E-W road. NW corner 10" concrete corner post SE 50.45. Meas west to CIM N 1/4 31 2621.9 (record 2611.6). Disc south side power pole 20482 SW 41.9. Disc SW side power pole 20492 NW 39.0.

6-11-1980 county highway department found CIM and took ties.

7-10-2002 County Surveyor found CIM in good condition.

5-12-2005 County Surveyor found CIM in good condition.