Certificate of Location of Government Corner

ID#: 723004 **Description:** 1/4 SEC COR 30 31 72 **Date Set:** 10/27/66 **County:** Olmsted

Section: 30 **Township:** 107N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 2' north of centerline of E-W twp road and 1' west of fence south
60d spike in SE side 14" Pine NE 58.3'
Bottle cap in W side CP S 37.6'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes: W.A. Jones, west random 30&31. 40.00 set a temp section post east on true line between section 30&31 38.86 set a sec post in mound of earth and sod. Depoisted charcoal, made trench and pitts, planted Osage Orange seeds N and S of trench.

9-1863 P.C. Compton P.77 No.114 shows 1/4 corner used to set center sec 31 at intersecting lines used to set property corner west.

5-1872 T. Hunter P.206 No.214 found fence post center road avered by E. Derby and J. Madden under oath that this post was replacement of original stake then in place set stone 2-1/2x7x20. Set stones west 5.91 for one then another 5.91 (390.0') for the other in line sec corner west (a stone) then 26.25 1732.5 west to sec cor total 2512.5. Meas east to sec cor stone 39.57. Set stake south 11.35 749.1 on N-S 1/4 line.

6-1873 T. Hunter P.227 No.230 found stone P.206

10-1966 J. Kerr dug for corner after meas from centerline road in line fence south west. On digging for corner found the bottom 6" of the recorded 2-1/2"x7" stone in the clay below road. Left pieces of this stone on E and W sides of 1-1/4x12" pipe with CIM on top. 60d on SE side 14" pine. The most westerly of row of pines NE 58.3'. Bottle cap on W side corner post S 37.6'. Corner lies 2' north centerline road and 1.0' west of fence line running south.

7-10-2002 County Surveyor found CIM in good condition.