Certificate of Location of Government Corner

ID#: 723005 **Description:** W SEC COR 30 31 72 **Date Set:** 7/11/2002 **County:** Olmsted

Section: 30 **Township:** 107N **Range:** 12W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 2 1/2' north of centerline of E-W twp road and 4 1/2' west of centerline of N-S twp road
County Survey Disk in PP NE 44.9'
This corner is located by GPS measurement

Corner History:

Gov't Notes: 80.00 set post and drove charred stake corner to section 25-30-31-36. Bur Oak 14 N13W. Bur Oak 15 S77W 81. Bur Oak 14 S7E 121. Bur Oak 12 N2E 70.

9-1863 P.C. Compton P.77 No.114 shows sec corner used to set property corner east.

5-1872 T. Hunter P.203 No.213 found old stake from stumps of B trees cut below mars but stake agreed with distances and bearings. Set boulder and stake by side. Meas south to stake set M&L 39.88 S 35' E. 1/16 west set stone 2x6x12 M&L 19.75 N89-1/2°W line south.

5-1872 T. Hunter P.206 No.214 found stone P.203. Meas south to stone set in place stake found 39.88 N1/4°E. Meas east 26.25 1732.5 to stone then 5.91 390.0' to another stone then 5.91 390.0' to N 1/4 31 now CIM.

6-1873 T. Hunter P.227 No.230 found stone set from stake P.203. Meas north to W 1/4 30 40.42 (see W 1/4 30).

5-1874 T. Hunter P.242 No.243 found stone P.203. 1/16 west found stone set P.203 used line north now no meas.

10-1966 J. Kerr set 120d as near corner 38 chs 2508.0' from N 1/4 31 recorded 2512.6 sec N 1/4 31. This 120d lies in centerline road east about 1.0' west of east edge road surface 6.5' east of centerline road south.

8-26-1968 J. Kerr found a stone monument 8 feet below the road surface. Set CIM over iron stone.

7-10-2002 County Surveyor found iron rod at corner location.

7-11-2002 County Surveyor set cast iron cap on telspar pipe at iron rod position.