Certificate of Location of Government Corner

ID#: 723006 **Description:** W 1/4 SEC COR 30 72 **Date Set:** 6/3/75 **County:** Olmsted

Section: 30 **Township:** 107N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in centerline of N-S twp road and 5 1/2' north of fence east
County Survey Disk in N side gate post NW 32.96'
County Survey Disk in S side of most southerly PP NW 274.8'
County Survey Disk in S side CP ESE 29.53'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes Ball, Deputy Surveyor North between sections 25 and 30 40.00 chs. Set post. Burr Oak 10" S11°W 40 lks. Burr Oak 8" N76°E 67 lks.

6-1873 Thomas Hunter (Pg. 227 No. 230), County Surveyor, states original corner missing. A Mr. Mark avers he helped set the corner post in the spot in the mound and pits where the original stake was pulled.

5-1874 T. Hunter (Pg. 242 No. 243) Round the marked corner fence post pg. 227.

7-1874 T. Hunter (Pg. 258 No. 259) used corner to set 1/16th East.

6-3-1975 County Surveyor dug with the backhoe and found a charred stake 2' deep and in the clay. (.5± North of prorated Hunter meas. and 1'± East of the line between the section corners). Set a C.I.M. over a 3/4" x 18" rod through the stake.

5-14-2002 County Surveyor found CIM down 0.8' in good condition.