Certificate of Location of Government Corner

ID#: 723106 **Description:** W 1/4 SEC COR 31 72 **Date Set:** 8/19/68 **County:** Olmsted

Section: 31 **Township:** 107N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in line with fence west and 4' west of centerline of N-S twp road
3/4" pipe W 49.90'
This corner is located by GPS measurement

Corner History:

Gov't Notes: 40.00 set post and drove charred stake for quarter section corner. Built mound, planted SE Osage Orange and NE Apple seeds.

9-1863 P.C. Compton P.77 No.115 shows 1/4 cor used to set 1/16 west M&L to center sec. 36 found.

5-1872 T. Hunter P.203 No.213 corner gone set stake M&L 39.88 N 35'E 2632.08. 1/16 west set stake M&L 19.81-1/2 N89°W

5-1872 T. Hunter P.206 No.214 found stake set P.203 set stone 3x6x16 in its place. Meas north and south now 39.88 2632.08 for line east sec center 31 for details.

10-1966 J. Kerr found original stake missed by Hunter 1872 also stone set M&L. Meas from 120d set centerline road E and sta. 2508 ± west of 1/4 30-31 set as near corner NW 31 south.

8-19-1968 J. Kerr set CIM over 5/8" iron at stone location.

7-1-1988 County Surveyor found CIM in good condition 4' west of centerline N-S twp rod. Took transit ties as corner maybe destroyed in regrading using J. Kerrs 1968 pipe 49.94' west corner is 4' W of centerline N-S twp road. Angle at J. Kerr RP pipe west of 1/4 cor. Angle RT shortest and most N'ly of two tower NW to W 1/4 31 Ave angle RT 137° 40' 45.5" chained 49.90'.

9-25-2006 County Surveyor found CIM down 0.6' in good condition. Did not look for reference pipe.