Certificate of Location of Government Corner

ID#: 723406 **Description:** 1/4 SEC COR 33 34 72 **Date Set:** 8/23/68 **County:** Olmsted

Section: 34 **Township:** 107N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The monument is down 1.0'
The corner falls in line with fence south
14" Burr Oak in fence line W 113.2'
Post with sign west 2.0
This corner is located by GPS measurement.

Corner History:

1853 Gov't Notes: W.A. Jones 40.00 set a section post. Bur Oak 9 in N35W 131 lks. Bur Oak 10 in. N40E 127 lks.

3-1879 T. Hunter P.354 No.346, corner gone but grubbed stump lying by hole grubbed from indicated corner as accepted fence corner of fence running north avered by Mr. Doty as set from corner. Set temp stake as corner, Doty avering to set stone as corner. Dist east to center tracks on exact 1/4 line 10.23-1/2. Dist east to RW west side of tracks a stake 9.41 a 50' RW. Bearing of line north N 25' E line east S89-1/2°E. Set stake on sec line north 23.00 which came 194 links from west RW of RR at 50' centerline track at right angle from centerline.

5-1880 John Fraser P.364 No.355 found old pit (either of B tree described or stone Doty P.354 promised to set) and on testimony of Doty set stone as corner. 1/16 north set stake M&L however meas of 39.97 quoted as not to be relied on by J. Fraser, typical.

8-23-1968 J. Kerr found limestone 2"x14"x7/12" on line fence south and west very near 621' from RR R/W. Set 12"x3/4" rod below. Set CIM well down 8" BT 113.2 west to 14" Burr Oak in fence line. Meas west 1301 to 1/16 fence north 2636 to 1/4 fences N and S.

6-30-2011 County survey crew found CIM in good condition.