Certificate of Location of Government Corner

ID#: 723506 **Description:** 1/4 SEC COR 34 35 72 **Date Set:** 6/16/88 **County:** Olmsted

Section: 35 **Township:** 107N **Range:** 12W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The monument is at the surface
The corner falls 1' north of fence east and 1' west of N-S fence
County Survey Disk in 10" CP E 1.43'
This corner is located by GPS measurement.

Corner History:

Gov't Notes W.A. Jones 1853 40.00 set a section post in mound of earth and soil. Deposited charcoal. Made trench & pitts planted Osage Orange seeds east and west of trench.

6-1882 Thomas Hunter Page 378 No. 369 and also old Field Book #5. Found original 1/4 post standing in mound - but pits obliterated. 1/16th North found stone planted with stake by its side. Set by some surveyor as a 1/16 Sec. Cor. This section having been at some time subdivided. Those adjoining and interested in the corner were satisfied with the corner. This found without measurements or tests. So we assumed it to be correct and used it as such.

6-16-1988 County Surveyor dug and found vertical limestone 3"x15"x12" with 2 limestones lying flat on north & south side, fd stake 8" long & 6" into clay below stone & NE of it. Set 5' long telspar/C.I.C. over stake found.

1-6-2011 County survey crew found cast iron cap on sq. pipe in good condition.