Certificate of Location of Government Corner

ID#: 723609 **Description:** SEC CEN 36 72 **Date Set:** **County:** Olmsted

Section: 36 **Township:** 107N **Range:** 12W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

Reference Ties:

The corner falls 1' SE of CP to fences N-S-W
This corner is located by GPS measurement

Corner History:

6-16-1893 W. Fraser P. 517 No. 483 set stone 2 x 12 x 18 at inters lines, 1/16 west set 2 stones 2 x 9 x 15 & 2 x 9 x 12 M & L 19.97-1/2, 1/16 north set stone 2 x 15 x 24 M & L 20.00, 1/16 south set stone 2 x 8 x 16 M & L 20.00, 1/16 east set temp stake M & L 19.95-1/2, 1/16 center NE 1/4 36 set stone 4 x 5 x 30 at inters lines.

11-24-1992 County Surveyor dug and found 2"x9"x17" limestone leaning slightly north with bottom flaring to 13" wide. Removed stone and dug around base found nothing. Reset stone in vertical position, with 1-1/2" iron down 8" on south side of stone for locating at a future time. The stone falls in line of fence west & 1' SE of corner post to fences N-S-W.

5-11-2007 Roger Brand and Associates used computed center at intersecting quarter lines.

7-13-2011 County survey crew found stone down 0.2' in good condition.