Certificate of Location of Government Corner

ID#: 730509 **Description:** SEC CEN 5 73 **Date Set:** 10/17/2005 **County:** Olmsted

Section: 05 **Township:** 107N **Range:** 13W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
Cast Iron Cap on telspar pipe

Reference Ties:

County Survey Disk in S side 20" Ash NE 14.61'
County Survey Disk in S side 30" Ash W 46.30'
Post w/sign 2' north
This corner is located by GPS reference stations "Wilder A & B"

Corner History:

3-27-1898 W. Fraser P.620, No.563, set stake & sandstone 6"x8"x20 at inter lines. 16W set stake M&L 20.01. 16N set stake and stone 2"x9"x24", 16E NW1/4 set stake inter lines.

10-30-1970 County Surveyor - found 1/16 stone south.

11-6-1970 County Surveyor found recorded stone 2' east corner post. Set 3/8"x4' steel post up 8". Left as is, came in bottom of deep ravine.

10-20-1982 McGhie & Betts found and used stone monument at center of section 5.

12-16-1983 V. Fangman found and used 1/2" pipe over limestone monument.

1-11-1991 McGhie & Betts found and used stone monument at center of section 5.

3-30-1992 Kleinschmidt Surveying found and used stone monument.

6-28-1994 R. Brand & Associates found and used stone monument.

10-17-2005 County Surveyor found 3/4" pipe up 0.2' leaning SE, took local ties and removed. Found stone down 1.8', took local ties and removed. Set 7' telspar w/CIC from ties taken from stone up 0.3'. CSD w/spike in south side of 20" Ash NE 14.61' and CSD with spike in south side of 30" Ash west 46.30'. Set sign and post 2.0' north.