# Certificate of Location of Government Corner

**ID#:** 730609 **Description:** SEC CEN 6 73 **Date Set:** 4/24/1959 **County:** Olmsted

**Section:** 06 **Township:** 107N **Range:** 13W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

County Surveyor recommends using the monumented center of section.

2" iron shaft

**Reference Ties:**

The corner falls under north-south fence and in line with fence east
Center 6" Cedar East 11.3'
Center 6" Cherry SE 83.1'
PK nail in NW side 8" Elm East 64.45'
This corner is located by GPS reference stations "Rock A & B"

**Corner History:**

4-9-1858 Thomas Hunter, (Book A, Page 53, Survey No. 77) shows center of section. 1/16th South set stake midway and on line at 19.88 chains (1312.08') to South 1/4. 1/16th North set stake on line at 20 chains (1320.00') then 19.98 chains (1318.68') to North 1/4.

4-15-1901 William Fraser, County Surveyor, (Book B, Page 5) could not find corner. 1/16th South could not find corner. 1/16th Center of SE 1/4 set small stake 20.00 chains (1320.00') west of 1/16th South of 1/4 Corner 5-6.

4-24-1959 McGhie & Betts, Inc. found 1-3/4" solid iron fence post as center of section.

1972 McGhie & Betts, Inc. used 2" steel post as corner. 1/16th North found 3/8" iron. 1/16th South set 5/8" pipe.

Mn/DOT shows iron shaft falls 1.1' east and 12.3' south of the computed intersection of quarter lines.

2-15-1980 McGhie & Betts, Inc. used monumented position.

6-28-1988 Yaggy Colby Associates found and used iron shaft.

7-26-1995 Vince Fangman found and used 1-3/4" iron shaft.

3-6-1996 Vince Fangman found and used 1-3/4" iron shaft.

6-27-1997 Vince Fangman found and used 1-3/4" iron shaft.

12-22-1997 McGhie & Betts, Inc. found 2" iron shaft up 4' and took new references.

6-15-2001 McGhie & Betts, Inc. used monumented position.

11-27-2002 County Survey Crew found 2" iron shaft up 4' in good condition and measured its position using GPS.

5-17-2004 GGG found and used iron shaft.

6-24-2004 Ed Kuisle, County Surveyor, found and used 2" iron shaft. He recommends using the monumented center of section based on historical use of this position.

12-20-2006 GGG found and used 2" iron shaft.

1-25-2007 GGG found and used 2" iron shaft.

10-19-2010 Brian Veronen, Mn/DOT LSIT, found 2" iron shaft in good condition and added a new reference.

12-8-2011 Mn/DOT found and used 2" iron shaft for Minnesota Department of Transportation Right of Way Plat No. 55-104.

2-1-2012  Mn/DOT found and used 2" iron shaft for Minnesota Department of Transportation Right of Way Plat No. 55-109.

10-2-2014  G-Cubed used 2" iron shaft.