Certificate of Location of Government Corner

ID#: 730705 **Description:** W SEC COR 7 18 73 **Date Set:** 11/29/1973 **County:** Olmsted

Section: 07 **Township:** 107N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls under N-S fence
County highway disk in 5" Cherry SE 16.10'
County highway disk in 10" Elm NW 29.55'
County highway disk in 6" Ironwood SW 19.41'
Post w/sign 1' SE
This corner is located by GPS reference stations "Big Log A & B"

Corner History:

1853 Gov't Notes John Ball, Deputy Surveyor North between sections 13 and 18. 80.00 chs. Set section corner post. Dug trench. Burr Oak 12 in. S17ºW 253 lks. Burr Oak 14 in. N0º5'W 1199 lks.

1858 T. Hunter Pg. 49 No. 72 used sec. corner 1/16 East 18.22 chs. then 20 chs. to 1/4 post.

Oct. 1859 T. Hunter Pg. 63 No. 89 shows sec. corner 1/16 North 19.96 chs., 1/16 south 20.04 chs. (See survey for S.E. 1/4 Sec. 12-107-14 & N.E. 1/4 Sec. 13 107-14).

8-1871 Robert Perry (P. 187 No. 198), found corner stake standing-bearing trees gone.

10-1877 Thomas Hunter (P. 322 No. 316), states corner gone. Set temporary stake by line and measure from W 1/4 cor. & over 1/16 corner south.

10-1887 Thomas Hunter (P. 322 No. 316), states corner gone. Set temporary stake by line and measure from W. 1/4 Cor. & over 1/16 corner South.

11-1888 T. Hunter (P. 187 caption) set quarry stone as corner, corner now limestone used recent surveys. RPs-center 18" CHERRY s 83.4', 1 1/4" PIPE s 10.4'. (Pipe set by McGhie 3-30-1948 and midwaybetween 1/4 corners N & S.

4-1954 John Kerr (Fieldbook No. 57 P. 74), County Surveyor, found corner and took cherry tree as witness tree.

11-29-1973 County Surveyor found nail set by Wallace, Holland, Kastler & Schmidts Co. in location of limestone they brought into the office. Set a C.I.M. over a 1/2"x18" rod as corner. RPs- 18.4' WSW to 60D north side 16" elm 32.3' SW to 40D east side 9" hackberry. 1 1/4" pipe up 2'.

12-12-1989 Wallace, Holland, Kastler & Schmidt found cast iron monument in N-S fence line.

12-17-1997 McGhie & Betts Found C.I.M. and post with sign and checked the references.

12-16-2003 County Surveyor found CIM down 0.1' in good condition. Removed 1 1/4" iron pipe next to CIM as well as old steel post in concrete.