Certificate of Location of Government Corner

ID#: 730809 **Description:** SEC CEN 8 73 **Date Set:** **County:** Olmsted

Section: 08 **Township:** 107N **Range:** 13W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

Reference Ties:

6" Oak (7" Burr Oak WNW 1976) NW 18.95'
14" Oak (28" Burr Oak WSW) SW 6.22'
14" Oak (22" Red Oak S) S 14.10'
This corner is located by GPS reference stations "Bowie A & B"

Corner History:

7-1870 - 1856 BK P.103 Rd. surface from E1/4 section 9 to center 8 from 1/4 8-9 to cen 8 = N 891/2°W 40, thence S 30.50 chains to 90° bend to west.

1959 McGhie set 5/8" rod (method unknown).

4-9-1963 J. Kerr found 5/8" rod at center of section 8.

1964 J. Kerr E1/4 8 to W1/4 8. Measure 527.82' set rod as SW corner REA at 1714.58' from E1/4 8.

3-1979 County Surveyor found 5/8" iron 2' north of E-W fences.

8-23-1982 Yaggy Associates used computed center.

9-24-1984 Yaggy Associates found and used 5/8" rod at center of section 8.

12-9-1988 V. Fangman found and used 5/8" rod at center of section 8.

6-25-1990 Land Consultants used computed center.

2-8-2001 Yaggy Colby used computed center.

10-19-2005 County Surveyor found 5/8" iron rod at surface in good condition. All tree's ok. Set sign and post 2.0' south in E-W fence.

7-5-2007 County Surveyor pulled out rerod and post w/sign.