Certificate of Location of Government Corner

ID#: 731006 **Description:** 1/4 SEC COR 9 10 73 **Date Set:** 11/24/1964 **County:** Olmsted

Section: 10 **Township:** 107N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 3' west of fence south
County highway disk in PP NW 47.0'
County highway disk in PP ESE 5.4'
This corner is located by GPS measurement

Corner History:

1853 Yerby, Gov't Notes, 40.00 set temp sec post. 12" Burr Oak S72 E89 links, 14" Burr Oak S46-1/2 W175 links.

5-16-1872 T. Hunter P.201, No.210 found stake from SE Bearing tree standing. Set stone in place of stake. 16 N set stake M&L 19.94'. 16 S set stake M&L 19.94'. 16 E set stake M&L 19.851/2'. 16 center NW1/4 1.0 set stake inter lines.

12-22-1932 County Highway Department (B72 P21), found and used stone monument for PI 218+78.5

11-24-1964 J. Kerr found stone in perfect form. Nail in hub - North side 20" Burr Oak E 71.8'. Fence running south E 3.0'. Measure north 2636.6 R 2632.08. Measure south 2636.6 to CIM set using above 1/4 corner as M&L. Measure west to center 9 set 2627.7. Set CIM over 3/4xe

3-20-1979 County Surveyor found CIM OK.

11-2-1989 County Surveyor found CIM & used in city mapping project survey.

8-1996 Peoples Coop found CIM 1'± NW of end post. About 1.2' deep.

1-17-2006 County Survey Crew found CIM down 1' in good condition.