Certificate of Location of Government Corner

ID#: 731404 **Description:** 1/4 SEC COR 14 23 73 **Date Set:** 6/8/1999 **County:** Olmsted

Section: 14 **Township:** 107N **Range:** 13W **Monument Description:** 5/8" copper plug with punch mark

Reference Ties:

The monument is at the surface
The corner falls in centerline of CSAH 2 and in centerline of field drive north
County Survey Disk in PP NE 86.68'
County highway disk in E side CP N 62.67'
NE cor house foundation SW 102.31'
County Survey Disk in PP #49538 NE 84.15'
This corner is located by GPS reference stations "Schmidt & PFCO"

Corner History:

1853 Gov't Notes, Yerby, 40.00 set temp sec post west on true line between sec 14 & 23 course 9° 02' E. 40.00 set sec post in trench & planted osage orange seeds N&S of trench.

6-23-1857 J. Fellows, Pg. 29, No.45, Set 1/16 corner N & set & used cen sec 14, the N-S 1/4 line S 0° 5'E.

4-1900 R. Fraser, P.663, No.590, found boulder 6"x12"x18".

8-6-1986 County Surveyor referenced County Highway Department POT spike. Dug with dozer 30' E-W centering on county highway department POT found where others had dug for corner.

6-8-1999 County Surveyor set 5/8" copper plug with punch mark at surface.

8-4-2011 County survey crew found brass plug with punchmark in good condition