Certificate of Location of Government Corner

ID#: 731604 **Description:** 1/4 SEC COR 16 21 73 **Date Set:** 11/8/2005 **County:** Olmsted

Section: 16 **Township:** 107N **Range:** 13W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 2 1/2' south of E-W fence
40d spike in NE side 3" tree up 10" ± ESE 4.4'
40d spike in NW side 9" Burr Oak NE 12.2'
40d spike in N side 14" Burr Oak WNW 8.4'
Post w/sign 2' north
This corner is located by GPS reference stations "Passe A & B"

Corner History:

1853 Gov't Notes, Yerby - 40.00 set temp set post west on true line between sec 16&21 course 8° 43' East. 39.96 set section post. 6" Burr Oak N45° W96 links. 6" Burr Oak S 48° E 151 links.

14-1858 T. Hunter, P.54, No.78, used corner - 2 org Bearing Trees. N 421/2°W .85 - S 45°E 1.58. 16E corner at M&L 19.84. 16W corner at M&L 19.75.

6-1876 T. Hunter (unrecorded survey field Bk.4 P. 140-141 & 176-177. Used something as N1/4 cor sec 21 - used to set center 21=P.140. P.177 shows 2 different sets of B.T. for 1/4 16-21. Bottom of P.177 at "L" = 1/4 16-21= Shows Bearing Trees 6" Burr Oak N45° W96 links. 6" Burr Oak S48° E151 links. Apparent Govt Bearing Trees as N 421/2°W 85 links & S45° E158 links. (Burr Oaks). Pg. 177 shows measure W as 19-75-1975.

5-1894 W. Fraser P.549, No. 507 set SE 17 by gov. records. Measure S 1/4 16 to SE 17 39.853/4 (2630.6)
Measure SE 17 to S1/4 17 39.923/4 (2635.2). S1/4 found remains of stake. Drove stake by in ground and set boulder beside it.

6-1896 T. Hunter P.602, No. 547 found original stake & stone. Bearing Trees gone. 16W set stone 2x10x24 M&L 19.93 (1315.4)

10-20-1972 County Surveyor found 1/16 cor at 1314.0. Set corner from correct offset. Set limestone 3"x13"x16" with 3/4"x18" iron beside it at final location.

11-8-2005 County Surveyor found 3/4" rerod up 0.1' in good condition w/stone on east side. Set 4 1/2' telspar pipe w/cast iron cap over 3/4" rerod up 0.3'. Set post w/sign.