Certificate of Location of Government Corner

ID#: 732005 **Description:** SEC COR 19 20 29 30 73 **Date Set:** 3/22/1977 **County:** Olmsted

Section: 20 **Township:** 107N **Range:** 13W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

County Survey Disk in W side (up 6') 6" blazed Burr Oak NNW 50.15'
Spike in NW side 15" Boxelder SW 5.03'
Spike in N side 11" Boxelder NW 8.63'
Post w/sign 2' west
This corner is located by GPS reference stations "Christmas Candy A & B"

Corner History:

1853 Gov. Notes, Yerby - 80.00 set sec cor post to section 19-20-29-30 in mound. Made trench, planted Osage Orange seeds NW & SE of trench.

6-1870 R. Perry, P.180, No.191 found original stake. 16N set stake M&L 19.95 (1316.7). 16E set stake M&L 20.0 (1320.0). 16C SW1/4 20 set stake M&L 19.94 (1316.04 on N-S 1/16 line).

4-1872 T. Hunter P.196, No.206 found stake. Measure north 39.90 to original corner (2633.4).
Measure W 40.30 to original corner (2659.8).

1-1878 T. Hunter, P.328 No.322 stone marked on plat - may not have used. Measure north on plat 39.911/2 (2634.39) to stake then measure 39.791/2 (2626.47 to section corner).

9-1891 T. Fraser, P.456 No.440, no mention of corner used - survey in SE1/4 30 caption W. Fraser 5-1894 below - couldn't find Hunter's stake. Set stone 6x8x18 by measure from 1/4 29-30 and NE corner 19 (stone in center mound) line short 431/2 links.

3-1900 W. Fraser P.661, No.588 found stone (claims stone set by measure between 1/4 29-30 and 1/4 19-20, measure North 39.911/2 (2634.4 then 39.791/2) (2637.36 to stake by post set M&L).

11-1959 McGhie - No stone found. Drove nail in Boxelder tree as corner, 2634 from 1/4 19-20.

6-15-1970 County Surveyor measure from pipe set by McGhie as 1/4 29-30, north record measure 39.851/2 (2634.3) Boxelder tree 2' to 3' in diameter. Stone may be gone. Nail should be accepted until proven different.

11-16-1972 County Surveyor dug for stone (found nothing).

3-22-1977 County Surveyor set Cast Iron Cap on telspar pipe by line and measurement from east.

7-2-2003 County Surveyor found cast iron cap on telspar pipe up 0.3' in good condition. Set post w/sign 2.0' West.