Certificate of Location of Government Corner

ID#: 732104 **Description:** 1/4 SEC COR 21 28 73 **Date Set:** 11/3/2005 **County:** Olmsted

Section: 21 **Township:** 107N **Range:** 13W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 1' south of E-W fence and 2' west of stub fence south
30d spike in S side 12" Oak E 7.33'
Post w/sign 2' south
This corner is located by GPS reference stations "Lofgren A & B"

Corner History:

1853 Gov't Notes, Yerby - 40.00 set temp sec post west on true line between sec. 21&28 8° 53'E. 39.99 set steel post, made trench. Burr Oak 8" 20W 272 links.

4-1858 T. Hunter, P.54 No.78 used corner - set 1/16 N M&L 19.82. 1/16 C SW1/4 21 measure N 19.83 (1308.78) e 19.72 (1301.52). 1/16 C SE1/4 21 measure N 19.8 (1306.8) W 19.75 (1303.5).

5-1876 T. Hunter P.23, No.36 org. Survey & caption 4-1857 & 5-1876. Found stake, avered by Cantz as true corner. Bearing Tree gone. 16S set marked stake M&L 19.85 to stone 2x8x24 set at center 28.

6-1896 T. Hunter P.602, No.547 found stake, 16W set stone 4x9x14 with stake by side M&L 19.951/4 (1316.86).

1909 C. Armstrong P.120B, set iron bar as 1/16 corner. 16E above 1/16 iron bar M&L 19.771/2 (1305.15) 16W set stone 3x10x14 M&L 20.031/2 (1322.3).

1962 J. Kerr, Center sec 28 - west stone by cor post at 1/16W - found stone.

11-1-1972 County Surveyor found stone. At 1/16 removed stone set in 1962 & placed on top of true stone with 1/2"x4" rod on north side of stone s witness centering stone E & W.

11-7-1972 County Surveyor found true 1/16 stone at 1316.9 R 1316.86, measure east and set 120D on proj. line. Drove nail on west side blazed 12" oak S 8.55.

5-10-1991 Vince Fangman used 120d spike for break down of section 28.

10-31-2005 County Surveyor found 120d spike down 0.2' in good condition.

11-3-2005 County Surveyor set 1' telspar pipe w/cast iron cap up 0.2' driven to refusal over 120d spike. Set post w/sign.