Certificate of Location of Government Corner

ID#: 732109 **Description:** SEC CEN 21 73 **Date Set:** **County:** Olmsted

Section: 21 **Township:** 107N **Range:** 13W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

Reference Ties:

Corner History:

4-14-1858 Thomas Hunter, (Book A, Page 54, Survey No.78) set stake at intersecting quarter lines. 1/16th South set stake midway and on line at 19.82 chains (1308.12') to South 1/4. 1/16th East set stake midway and on line at 19.70 chains (1300.20') to East 1/4. 1/16th West set stake midway and on line at 19.72 chains (1301.52') to West 1/4. 1/16th Center of SW 1/4 set stake at intersecting sixteenth lines. 1/16th Center of SE 1/4 set stake at intersecting sixteenth lines.

6-28-1876 Thomas Hunter, County Surveyor, (Old Field Book #4, Pages 140-141) measured east 19.88 chains (1312.08') and measured west 19.90 chains (1313.40').

9-12-1899 Robert Fraser, Deputy County Surveyor, (Book A, Page 644, Survey No. 580) 1/16th South found remains of old stake. 1/16th Center of SE 1/4 dug and found remains of old stake.

8-19-1977 Thomas Taylor Co. used computed center at intersecting quarter lines.

1-18-1995 Land Consultants used computed center at intersecting quarter lines.

12-14-1998 Land Consultants used computed center at intersecting quarter lines.

1-19-1999 Land Consultants used computed center at intersecting quarter lines.

11-26-2007 Massey Land Surveying used computed center at intersecting quarter lines.

6-21-2016 G-Cubed used computed center at intersecting quarter lines.