Certificate of Location of Government Corner

ID#: 732205 **Description:** SEC COR 21 22 27 28 73 **Date Set:** 6/3/1966 **County:** Olmsted

Section: 22 **Township:** 107N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in line with fence north, 2' south of E-W fence and 19' west of fence south
PK nail in W side PP (up 1') NNE 42.90'
Post w/sign 2' north
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes, Yerby - 80.00 set corner post to sec. 21,22,27&28, made trench, planted Osage Orange NW & SE of trench.

1858 T. Hunter, Pg.54, No.78 Measure North 39.57 chains.

5-1889 T. Fraser P.429 No.417 found stake remains. Set marked stake & stone 4x7x16. Measure south 39.811/4 (2627.6').

9-1899 R. Fraser P. 644 No. 580 found stake and stone, P.429. 16 North drove cedar stake M&L 19.873/4 (1311.9'). 16C west, this center SE21 M&L 19.757/8.

1909 Charles Armstrong, P.120 B found stone. 16 North found cedar stake at fence corner M&L 19.84 (1309.44). 16C SE1/4 S21 set iron bar as corner M&L 1305.15. Found R. Fraser's stake north of point set 3" corner, as set 6" NE of 10" Burr Oak tree 10" diameter.

6-1966 J. Kerr found stone 3x11x13, set CIM over 11/2"x17" pipe which is below original stone with beer can and wood hub by side of corner. Nail & hub south side tele pole stub as anchor post of woven wire E 5.85'.

1974 County Surveyor took new reference to CIM, CSD in S side of P.P. SE 11.4'.

8-1996 Dean Strange of Peoples Coop found CIM at the surface.

1-29-2002 Roger Brand found CIM in good condition 6" deep in washed in area and took new references.

11-4-2005 County Surveyor found CIM down 1' in good condition.